



346020

bticino

Additional power supply to be used to supply entrance panels and internal units locally. 2 DIN modular enclosure. Power supply 230 Vac at 50-60 Hz. The output provides 27 Vdc continuous low voltage, with maximum current of 600 mA and it is protected on the PRI side (with fuse) against overload and short circuit. It is a SELV double insulation safety device.

Technical features

Brand	BTicino
Reference Standard	CEI EN60065
Rated voltage	220-230Vac
Input current	600mA
Rated power (W)	3.8W
Modules	2
Plant type	SCS-BUS
insertion	2 fili / 2Wires
Operating temperature	5 - 40°C
Series	Accessories

Commercial data

Minimum quantity	1
Sales unit	1
EAN code	8012199955933

Technical documentation

? Technical Data Sheet

? Instruction Sheet

? DWG drawing

We, BTicino S.p.A. Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Certifications



Complete with



308001
Linea 300 monobloc
vandal-resistant 2 wi...



308002
Monobloc vandal-resistant
2 wires video ...



308003
Monobloc vandal-resistant
2 wires video ...



308004
Monobloc vandal-resistant
2 wires video ...



308005
Monobloc vandal-resistant
2 wires video ...



308011
Monobloc vandal-resistant
2 wires video ...



308012
Monobloc vandal-resistant
2 wires video ...



308013
Monobloc vandal-resistant
2 wires video ...



308014
Monobloc vandal-resistant
2 wires video ...



308015
Monobloc vandal-resistant
2 wires video ...



344642
Connected 2 wire / Wi-Fi
handsfree vide...



344643
Connected 2 wire / Wi-Fi
handsfree vide...



346310
Guard station for 2 wires
audio and vide...



L4669KM1
Sheathed pair made up of 2
flexible wire...



L4669
Sheathed pair made up of 2
flexible wire...



336904
Specific BUS/SCS cable,
unshielded, cons...



336905
Specific BUS/SCS cable,
unshielded, cons...



344682
Classe 100X16E with
Netatmo 2 wires / Wi...



364932
One-family handsfree kit
with: Classe 10...



344842
2 wires/Wi-Fi handsfree
connected video ...



363915
One-family handsfree kit
with Classe 300...



363950
One-family kit with Classe
300EOS handsf...



344672
Classe 100 2 wires
handsfree video inter...



344884
2 wires/Wi-Fi handsfree
connected video ...

**363926**One-family video kit with
connected Clas...