



E46ADCN





Power supply - input 230 Vac, output 27 Vdc SELV - maximum consumption 450 mA – DIN rail mounted model - space requirement 8 DIN modules – for flush mounted or wall mounted switchboards

Technical features

| Brand | BTicino |
|--------------------|----------------------------------|
| Reference Standard | EN 60669-2-1EN 50491-5-1EN 50428 |
| Rated voltage | 230Vac |
| Input current | 300mA |
| Modules | 8 |
| Height | 90mm |
| Width | 143mm |
| Depth | 60mm |
| Series | MyHome |

Technical documentation

? DWG drawing ? Instruction Sheet

? Product Environmental Profi le

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Certifications





GENERAL CATALOGUE

Complete with



 $\begin{array}{c} L4669KM1 \\ \text{Sheathed pair made up of 2} \end{array}$ flexible wire...



 $L4669 \\ \text{Sheathed pair made up of 2}$ flexible wire...



 $\begin{array}{c} 336904 \\ \text{Specific BUS/SCS cable,} \end{array}$ unshielded, cons...



 $\begin{array}{c} 336905 \\ \text{Specific BUS/SCS cable,} \end{array}$ unshielded, cons...



Alternative solutions



E56

Power supply with input voltage 110 – 24...