

# 150705



Underfloor boxes 24/30 modules - compartment cover with customizable and ergonomic handle

## Technical features

Brand BTicino

Modules 24-30

Height 92.5mm

Width 441mm

Depth 270mm

Series

## Commercial data

Minimum quantity 1

Sales unit 1

EAN code 8012199779720

## Technical documentation

[↓ Instruction Sheet](#)

[↓ DWG drawing](#)

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

**Complete with****150712**Support for 5 modules  
LivingLight and Lu...**150713**Support for 4 modules  
Matix to use in un...**150715**Support for 5 connectors  
RJ45 IDC110 typ...**150716**Support for 2 modular  
DIN35 rail device...**150717**Blanking module  
support...**150718**Internal partition for  
item 150712 and i...**150719**Pre-wired module -  
cannot be installed i...**150569S**Galvanised aluminium  
flush mounting boxe...**150720**Support for 5 connectors  
type RJ45 or ty...