





# 308014



Monobloc vandal-resistant 2 wires video entrance panel for 20 calls with stainless steel finish. The item code includes: flush mounted box, frame, colour video and audio electronic module, prewired pushbutton module/s. Presetting for the mounting of transponder reader or key switch. Backlit call keys. Visual and sound notifications of the communication status for: call active, system busy, door lock status

#### Technical features

Brand	BTicino
Protection class	IP54
Dimensions	440x180mm
Height	440mm
Width	180mm
Calls	20
Plant type	2 fili / 2Wires
Robustness	IK07



## **GENERAL CATALOGUE**

Installation height	160-165cm	Commercial data	
Operating temperature	-25° - +70°C	Minimum quantity	1
Resolution	330 Linee H / 330 Lines H	Sales unit	1
Colour	Inox finish / Finitura Inox	EAN code	8012199995335
Series	Linea 300		

#### Technical documentation

- ? Technical Data Sheet
- ? DWG drawing

? Instruction Sheet

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

## Complete with



