



336904



Specific BUS/SCS cable, unshielded, consisting of a white external sheath and 2 x 0.50 mm² brown and brown/white twisted flexible conductors. Insulation 400 V. In compliance with the standards: EN50575 EN60811, EN50289, EN50290, EN60228, EN50265-2-1, EN50395, EN50396 as described in the IMQ CPT 062 document. Cable suitable for underground installation inside appropriate conduits (for the details see the technical sheet). Coil length 200 m. Class of reaction to fire according to the CPR Regulation: Eca.

Technical features

Brand	BTicino
Length	200m
Series	Accessories

Commercial data

Minimum quantity	1
Sales unit	1
EAN code	8012199654362

Technical documentation

- ? Product Performance Declaration
- ? Product Environmental Profile

- ? Technical Data Sheet

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Complete with



346020
Additional power supply to be used to su...



E46ADCN/127
Power supply - input 127 Vac, output 27 ...



E49
Compact power supply for Temperature con...



E56
Power supply with input voltage 110 – 24...

Alternative solutions



336905
Specific BUS/SCS cable, unshielded, cons...