



336905



Specific BUS/SCS cable, unshielded, consisting of a white external sheath and 2 x 0.50 mm² brown and brown/white twisted flexible conductors. Halogen-free Low toxicity cable; ideal for applications where fire safety is particularly critical. Insulation 400 V. In compliance with the standards: EN 50575 EN60811, EN50289, EN50290, EN60228, 50265-2-1, EN50395, EN50396 as described in the IMQ CPT 062 document Cable not suitable for underground installation. Coil length 200 m. Class of reaction to fire according to the CPR regulation: Cca-s1b,d1,a1.

Technical features

Brand	BTicino
Lenght	200m
Series	Accessories

Commercial data

Minimum quantity	200
Sales unit	200
EAN code	8005543621516

Technical documentation

? Declaration of Performance

? Technical Data Sheet

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Complete with



E49

Compact power supply for Temperature con...



346020

Additional power supply to be used to su...



E46ADCN/127

Power supply - input 127 Vac, output 27 ...