



343062

2-Wires video entrance panel for surface- or flush-mount installation, featuring a black aluminum front plate and a 2 MP colour camera with $\pm 15^\circ$ tilt adjustment on both vertical and horizontal axes. Equipped with an integrated brightness sensor for nighttime backlighting of name tags and white LEDs to illuminate the field of view in low-light conditions. Configurable for single- or two-family setups via the two front buttons. Supports activation of an electric lock connected directly to the S+ and S- terminals (18 V, 4 A impulse; 250 mA holding current; max 30 ?). Relay terminals (C/NC/NO) are also provided for managing a second lock. Rated IP44 for protection. Compatible with the BT-332710 flush-mount box.

Technical features

Brand	BTicino
Rated voltage	18-27 Vdc
Protection class	IP44
Dimensions	99 x 245 x 36mm
Height	245mm
Width	99mm
Depth	36mm
Calls	2
Plant type	2 fili / 2Wires
Robustness	IK03

Installation height	160-165cm
Operating temperature	-25° - +70°C
Field of view	110°
Series	LINEA 2000L

Commercial data

Minimum quantity	1
Sales unit	1
EAN code	8005543811283

Technical documentation

[? Instructions](#)
[? Technical sheet](#)

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Complete with


346250

Relay module for gate opening to be used...


332710

Flush-mounted box for Linea 2000L2 and L...

Alternative solutions


343064

2-Wires video entrance panel for surface...