



345000

bticino

Display and audio/video module to be combined with one of the 5 frames in different finishes for the creation of 2 wires systems. Equipped with a 5 MP HQ camera with wide-angle field of view (119° horizontal - 92° vertical), white LEDs for lighting and twilight sensor for night vision. High-resolution 7" touch screen display with shatter-proof glass (IK08), anti-fingerprint and proximity sensor for automatic switching on. With a digital microphone and echo eliminator for optimal sound performance. The flexible and user-friendly graphic interface is adaptable to any type of apartment block and allows a choice of 3 different call modes: address book call (list of residents' names), numeric or alphanumeric code call and block-staircase-floor-apartment logic code call. The direct call to the guard station and the customisation of the homepage logos also make it suitable for solutions with concierge or for commercial establishments. With advanced features such as voice feedback, automatic theme change (light/dark), customisation of welcome messages or instructions and temporary access code forwarding, it is suitable for residents and visitors of all ages and abilities. It also supports different modes for accessing the building: lock release with display code, RFID badge or Bluetooth via the Home + Security App, the resident's app. Programming and configuration requires the use of Home + Project (App or PC), the digital tool for the professional. Using this tool, it is possible to complete the entire configuration at the office, share it with other professionals and upload it to the display module via Bluetooth. Changes to residents' names and access codes are quick and smart, either on-site (via Bluetooth) or remotely (if the module has an active WiFi or Ethernet connection). Installation with 3-module flush-mounted box 350030 or with wall-mounted box 345331 or 345332. The book-like opening of the module allows for easy wiring. It allows the activation of an electrical door lock directly connected to clamps S+ and S- (18 V 4 A impulsive - 250 mA holding current 30 Ohm max) and of connecting a local door lock release pushbutton on clamps PL.

Technical features

Brand	BTicino
Rated voltage	18-27 Vdc
Modules	3
Protection class	IP65
Dimensions	128x354x42 mm
Height	354 mm
Width	128 mm
Depth	42 mm
Plant type	2 wires
Robustness	IK08

Installation height	180cm
Operating temperature	(-25) – (+70) °C
Connection type	BUS SCS
Resolution	625 Linee TV (H)
Series	LINEA 5000

Commercial data


Minimum quantity	1
Sales unit	1
EAN code	8005543746073

Technical documentation


- ? Instructions
- ? Installation and configuration manual
- ? Technical sheet

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Complete with




345101
3-module frame in
aluminum (60% recycle...)




345102
3-module frame in
aluminium (60% recycle...)



345103
3-module frame in
aluminium (60% recycle...)



345104
3-module frame in
aluminium (60% recycle...)



345105
3-module frame in
aluminium (60% recycle...)



350030
Flush-mounting box 3
modules for Sfera a...



345331
Wall-mounting box with
integrated rainsh...



345332
Wall-mounting box with
integrated rainsh...



345111
XL accessory plate in
aluminium finish u...



345112
XL accessory plate in
nickel finish used...




345121
Accessory plate in
aluminium finish comp...




345122
Accessory plate in nickel
finish compati...




SP115
LINEA 5000 Spare part – 3
modules alumin...




V/345102
3-module frame that can be
customised wi...




V/345103
3-module frame that can be
customised wi...



V/345101
3-module frame that can be
customised wi...



V/345104
3-module frame that can be
customised wi...



V/345105
3-module frame that can be
customised wi...



348200
Door opening RFID
transponder black key ...



348201
Door opening RFID
transponder red key fo...



348202
Door opening RFID
transponder green key ...



348203
Door opening RFID
transponder blue key f...



348204
Door opening RFID
transponder orange key...



348205
Door opening RFID
transponder grey key f...



348206
Door opening RFID
transponder yellow key...



3547
Hotel Room Management -
Badge in credit ...