





346020



Additional power supply to be used to supply entrance panels and internal units locally. 2 DIN modular enclosure. Power supply 230 Vac at 50-60 Hz. The output provides 27 Vdc continuous low voltage, with maximum current of 600 mA and it is protected on the PRI side (with fuse) against overload and short circuit. It is a SELV double insulation safety device.

Technical features

Brand BTicino Reference Standard **CEI EN60065** Rated voltage 220-230Vac Input current 600mA Rated power (W) 3.8W 2 Modules Plant type **SCS-BUS** insertion 2 fili / 2Wires Operating temperature 5 - 40°C Series Accessories

Commercial data

Minimum quantity	1
Sales unit	1
EAN code	8012199955933

Technical documentation

? Technical Data Sheet

? DWG drawing

? Instruction Sheet

We, BTicino S,p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S,p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.



GENERAL CATALOGUE

Complete with



308001 Linea 300 monobloc vandal-resistant 2 wi...



308002 Monobloc vandal-resistant 2 wires video ...



308003 Monobloc vandal-resistant 2 wires video ...



308004 Monobloc vandal-resistant 2 wires video ...



Monobloc vandal-resistant 2 wires video ...



Monobloc vandal-resistant 2 wires video ...



308012 Monobloc vandal-resistant 2 wires video ...



308013 Monobloc vandal-resistant 2 wires video ...



308014 Monobloc vandal-resistant 2 wires video ...



308015 Monobloc vandal-resistant 2 wires video ...



344642 Connected 2 wire / Wi-Fi handsfree vide...



344643 Connected 2 wire / Wi-Fi handsfree vide...



 $\begin{array}{l} 346310 \\ \text{Guard station for 2 wires} \\ \text{audio and vide...} \end{array}$



L4669KM1 Sheathed pair made up of 2 flexible wire...




L4669 Sheathed pair made up of 2 flexible wire...



336904 Specific BUS/SCS cable, unshielded, cons...



336905 Specific BUS/SCS cable, unshielded, cons...



344682 Classe 100X16E with Netatmo 2 wires / Wi...



364932 One-family handsfree kit with: Classe 10...



344842 2 wires/Wi-Fi handsfree connected video ...



363915 One-family handsfree kit with Classe 300...



344672 Classe 100 2 wires handsfree video inter...



344884 2 wires/Wi-Fi handsfree connected video ...



363926 One-family video kit with connected Clas...