



351100

bticino

Speaker module suitable for 2 wires audio & video systems. Fitted with loudspeaker and microphone volume adjustment. It can manage up to 100 pushbutton calls when using additional double row pushbutton modules. It can be used for opening an electrical door lock directly connected to the S+ and S- clamps (18 V 4 A impulsive - 250 mA holding current 30 Ohm max) and the connection to a local door lock release pushbutton on the PL clamps. Preset for additional power supply. Fitted with front LEDs for the notification of the operating status: door lock release, communication active, call put through, and system busy. Integrated optic sensor for the switching on of the night backlighting. To be completed with surround plate. The device can be configured either physically or using the PC and the TiSferaDesign software.

Technical features

Brand	BTicino
Modules	1
Height	91mm
Width	115mm
Calls	4
Plant type	2 fili / 2Wires
Operating temperature	-25° - +70°C
Series	Sfera

Commercial data

Minimum quantity	1
Sales unit	1
EAN code	8005543441558

Technical documentation

? Instruction Sheet	? DWG drawing
? Software Manual	? Technical Datasheet

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Complete with


346993

Sfera expander button module. Allows you...


346250

Relay module for gate opening to be used...


351105

Sfera New speaker module front cover - R...


351102

Sfera New speaker module front cover - A...


351103

Sfera New speaker module front cover - A...


351101

Sfera New speaker module front cover - A...


351111

Sfera New speaker module front cover, 1 ...


351113

Sfera New speaker module front cover, 1 ...


351112

Sfera New speaker module front cover, 1 ...


351115

Sfera New speaker module front cover, 1 ...


351121

Sfera New speaker module front cover, 2 ...


351123

Sfera New speaker module front cover, 2 ...


351122

Sfera New speaker module front cover, 2 ...


351125

Sfera New speaker module front cover, 2 ...


351141

Sfera New speaker module f/cover, 2 push...


351143

Sfera New speaker module f/cover, 2 push...


351142

Sfera New speaker module f/cover, 2 push...


351145

Sfera New speaker module f/cover, 2 push...


351181

Sfera New speaker module f/cover, 4 push...


351183

Sfera New speaker module f/cover, 4 push...


351182

Sfera New speaker module f/cover, 4 push...


351185

Sfera New speaker module f/cover, 4 push...