



374006

bticino

Small video entrance panel with RFID badge reader and key for indoor unit and guard station calls. The small video entrance panel can be PoE (power over Ethernet) powered, or directly powered using power supply BT-375005. Wall mounted installation thanks to the support with rainshield included.

Technical features

Brand	BTicino
Rated voltage	24Vdc
Protection class	IP54
Dimensions	100x160.5x36mm
Height	160.5mm
Width	100mm
Depth	36mm
Plant type	IP
insertion	RJ45
Robustness	IK07

Cable cross section	0.8mm
Installation height	160-165cm
Operating temperature	-40 - +70°C
Colour	Nero - Black
Series	IP Door Entry System

Commercial data

Minimum quantity	1
Sales unit	1
EAN code	8005543732304

Technical documentation

? Instructions

? Installer Manual

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.