

Distributed by BTicino GENERAL CATALOGUE



375010



Lift control interface with protocol translator to integrate lift function in IP door entry system. The configuration is completed using a dedicated software, the interface is connected via RS 485 cable to the entrance panel and the lift.

Commercial data

Technical features

| Brand | BTicino | Minimum quantity | 1 |
|---------------|----------------------|------------------|---------------|
| Rated voltage | 9-24Vdc | Sales unit | 1 |
| Modules | 4 | EAN code | 8005543693711 |
| Dimensions | 72x105x33mm | | |
| Height | 105mm | | |
| Width | 72mm | | |
| Depth | 33mm | | |
| Plant type | IP | | |
| Series | IP Door Entry System | | |
| | | | |

Technical documentation

- ? Software Manual
- ? Technical Data Sheet

- ? Installer Manual
- ? Instruction sheet

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1999 "R&CTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.