





AM5659



Matix passive infrared sensor for detecting motion and the lighting level. of wide covering area 5 m for 180 $^{\circ}$ and depth of field of 9 m and a height of 1.2 m installation. Timing for switch-off delay and threshold of the light sensor can be set by remote control BMSO4 series - 2 modules.

Technical features

Brand	BTicino
Rated voltage	27Vdc
Input current	15mA
Modules	2
Protection class	IP20
Robustness	IK04





GENERAL CATALOGUE

Illuminance level	20-1275 lux	Commercial data	
Operating temperature	-5°C +45°C	Minimum quantity	1
Colour	Bianco	Sales unit	1
Series	MyHome	EAN code	8005543479018

Technical documentation

? DWG drawing

? Instruction Sheet

? Technical Data Sheet

We, BTicino S,p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S,p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.