



## BMDI3101



Room Controller SCS dimmer DALI, “Zero Crossing” technology, 4 output with maximum load 16 ballast at 230Vac with screw connection 4 inputs Bus for sensors and commands connection SCS with BUS maximum consumption 200 mA and terminal connection and RJ45, 1 input Bus SCS with terminal connection and RJ45, power supply 100/240Vac 50/60 Hz, protection degree IP20, ceiling installation automatic configuration Plug&Go, pushbutton for Push&Learn procedure, pushbutton for direct command of the load

### Technical features

Brand BTicino

Series Stand alone solutions for lighting management

### Technical documentation

? DWG drawing

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 “R&TTE” or where requested also in compliance with 2014/53/EU: 16 April 2014 “RED”. BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.