



## BMSA1104



Switch Sensor with passive infrared, for the movement detection and the level of illumination, “Zero Crossing” technology, ON/OFF management wall and ceiling installation, protection degree IP42, screw terminal connection, covering area 6 m for 140° and field depth 8 m for 2.5m (installation height), maximum height of installation 6 m, power supply 100-240Vac, 50/60 Hz, maximum load 4.3 A at 230Vac, luminance level setting by trimmer from 10 lux to 1275 lux and delay time from 10 s to 10 min

### Technical features

Brand	BTicino
Rated voltage	240Vac
Frequency	50-60Hz
Contact type	4,3 A
Protection class	IP42
Width	84mm
Length	149mm
Depth	46mm
Illuminance level	10-1275 lux
Colour	Bianco
Series	Stand alone solutions for lighting management

### Commercial data

Minimum quantity	2
Sales unit	2
EAN code	8005543556870

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 “R&TTE” or where requested also in compliance with 2014/53/EU: 16 April 2014 “RED”. BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.