



## BMSA2106



Switch Sensor with passive infrared equipped with long range lens, for the movement detection and the level of illumination, “Zero Crossing” technology, ON/OFF management, wall or ceiling installation, protection degree IP42, screw terminal connection, covering area 6 m for 180° and depth field of 25 m for an height of 2.5 m, maximum installation height 6 m, power supply 100-240Vac, 50/60 Hz, maximum load 8.5 A at 230Vac, setting by remote control item BMSO4003 or BMSO4001 of the luminance level from 5 lux to 1275 lux and delay time from 5 s to 59 min

### Technical features

Brand	BTicino
Series	Stand alone solutions for lighting management

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 “R&TTE” or where requested also in compliance with 2014/53/EU: 16 April 2014 “RED”. BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.