





BMSW3003



Room Controller SCS ON-OFF, dimmer 1/10V and for automation, "Zero Crossing" technology, 4 outputs, 1 output for automation maximum load 2.1 A at 230Vac, 2 output ON-OFF 16 A at 230Vac and 2 output 1-10V 4.3 A at 230Vac with screw connection 4 inputs Bus SCS for sensors and commands connection, BUS maximum consumption 200 mA, terminal connection and RJ45, 1 input Bus SCS with terminal connection and RJ45, power supply 100/240Vac 50/60 Hz, protection degree IP20, ceiling installation, automatic configuration Plug&Go, pushbutton for Push&Learn procedure, pushbutton for direct command of the load

Technical features

Brand BTicino

Series Stand alone solutions for lighting management

Technical documentation

? DWG drawing

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.