



E56



Power supply with input voltage 110 – 240Va.c. @ 50 – 60 Hz. The output provides two power supplies in very low safety voltage (one of 27V d.c 1.2A on the SCS terminals, one of 28,5V d.c. on terminal 1 - 2) to be used alternately and NOT at the same time. It can also be used as additional power supply (1 - 2 output) for the local power supply of the automation devices (in this case it is not possible to use other outputs). The device is electronically protected against overload and short circuit. It is a SELV double insulation safety device - Size 6 DIN modules.

Technical features

| | |
|---------------|---------|
| Brand | BTicino |
| Rated voltage | 27Vdc |
| Input current | 1.2A |
| Modules | 6 |
| Series | MyHome |

Commercial data

| | |
|------------------|---------------|
| Minimum quantity | 1 |
| Sales unit | 1 |
| EAN code | 8005543693629 |

Technical documentation

[? Technical Datasheet](#)
[? Instruction Sheet](#)

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Complete with


L4669KM1

Sheathed pair made up of 2 flexible wire...


L4669

Sheathed pair made up of 2 flexible wire...


L4669/500

Sheathed pair made up of 2 flexible wire...


336904

Specific BUS/SCS cable, unshielded, cons...