



F10AXC2

Module surge protection device (SPD) - 1P+N - Type T2 -
 $I_{max}=20kA$ - $U_p=1,2kV$ - $U_c=320Vac$ - 2+2 modules - with
 auxiliary contact

Technical features

Brand	BTicino
Reference Standard	EN 61643-11 - IEC 61643-1
Max discharge current	20kA
Modules	4
Poles	1P+N
Contact type	1NO/NC
Protection class	IP20
Height	86mm
Width	71.2mm
Depth	68mm
Maximum cable section	16/25mmq
Series	Btdin

Technical documentation

? Instruction Sheet

? Technical Data Sheet

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Complete with



F10A

Replaceable cartridge for
SPD items F10A...