



F305PT54

Wall mounted switchboard with box and transparent door, 54 x DIN35 modules (600x450x150mm). Compliance with regulations IEC 60670-24 , CEI 23-48 , CEI 23-49, CEI 61439-3. IP40 and IK07 (6 joule) protection index. Material in thermoplastic resin. Insulating class II. RAL 9003 white wall mounted box. Operating temperature: -10 to 60 °C. Resistance to abnormal heat and fire (EN 60695-2-11): 650 °C. DIN35 rail type: Galvanized steel. Preset cut-outs for pipes (diameter) 16-32mm. Reversible door opening. Wall mounted box supplied

Technical features

Brand	BTicino
Reference Standard	IEC 60670-24 , CEI 23-48 , CEI 23-49, CEI 61439-3
Rated power (W)	66W
Modules	3x18
Protection class	IP40-IK07
Height	600mm
Width	450mm
Depth	150mm
Series	Linea Wall

Commercial data

Minimum quantity	1
Sales unit	1
EAN code	8005543545843

Technical documentation

? [Technical Data Sheet](#)

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Certifications



Complete with



F305B54
RAL9003 white door for
LINEA WALL wall m...



F215FP
Blanking module front
cover with 6.5 DIN...



F305C1
Key door lock for Linea
Wall switchboard...



F305KM
Wall fixing brackets for
switchboards wi...



F305PF18
Perforated device holder
plate for 36 - ...



F305PP18
Solid plate for 36 - 54 and
72 DIN modul...



F305TP
Document holder pocket...