



## F411U2



Actuator 2-channels management of LED lamps , compact fluorescent lamps ( CFL ) , linear fluorescent with electronic transformers and ferromagnetic transformers. Each channel is capable of switching up to a maximum of 10A . The device incorporates the function Zero crossing for proper management of energy-saving lamps - 10A incandescent lamps , fluorescent lamps 4A . and ferromagnetic transformers , fluorescent lamps 2A . compact LED - 2 DIN modules

### Technical features

Brand	BTicino
Rated voltage	27Vdc
Input current	55mA
Rated power (W)	1380W
Rated power (VA)	460VA
Modules	2
Contact type	2
Series	MyHome

### Commercial data

Minimum quantity	1
Sales unit	1
EAN code	8005543533871

### Technical documentation

? Technical Data Sheet

? Technical Data Sheet

? Product Environmental Profile

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU; 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU; 26 February 2014, and/or where requested also in compliance with 1995/5/CE; 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU; 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.