





F413N



1 output dimmer for the powering of fluorescent lamps or LED sources with 1 to 10 V input for single loads up to 2.5 A at 230 Vac - screw connection - 27 Vdc power supply - absorption 30 mA - possibility of connecting up to 10 ballasts (clamps 1-2) - with direct load control pushbutton - DIN rail mounted version - 2 modules

Technical features

Brand	BTicino
Rated voltage	27Vdc
Input current	30mA
Rated power (W)	460W
Modules	2
Protection class	IP20
Operating temperature	-5°C +45°C
Series	MyHome

Commercial data

Minimum quantity	1
Sales unit	1
EAN code	8012199894461

Technical documentation

? Technical Data Sheet

? Instruction Sheet

? DWG drawing

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.