



F418U2

Dimmer two channels for managing dimmable LED, dimmable compact fluorescent lamps CFL, halogen and energy-saving electronic transformers at 110-230V. Possibility of parallelization of the two channels to increase the maximum power handling. Power 27 Vd.c., absorption 18 mA - for securing execution on DIN - 4 modules

Technical features

Brand	BTicino
Rated voltage	27Vdc
Input current	18mA
Rated power (W)	2x300W
Rated power (VA)	2x300VA
Modules	4
Series	MyHome

Commercial data

Minimum quantity	1
Sales unit	1
EAN code	8005543534991

Technical documentation

? Technical Data Sheet

? Instruction Sheet

We, BTicino S.p.A. Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU; 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU; 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.