



F430/2



2 independent relay actuator – for single and double loads: 6 A resistive, 2 A motor valves and pumps - logic relay interlock via configuration - 2 DIN modules

Technical features

Brand	BTicino
Reference Standard	EN 60669-2-1EN 50491-5-1EN 50428
Rated voltage	27Vdc
Input current	25mA
Rated power (W)	1,7W
Modules	2
Contact type	2
Height	90mm
Series	MyHome

Commercial data

Minimum quantity	1
Sales unit	1
EAN code	8012199667690

Technical documentation

- ? DWG drawing
- ? Technical Data Sheet
- ? Technical Data Sheet

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Complete with



KW4691

Probe with backlit display
that controls...



KG4691

Probe with backlit display
that controls...



KM4691

Probe with backlit display
that controls...



H4691

Flush mounted thermostat
with backlit di...



LN4691

Flush mounted thermostat
with backlit di...