



F80GC



Load management module. Device for the management of electric loads that gives the possibility of controlling the power engaged, activating, in case of overload, an internal acoustic signal (buzzer) and, if set accordingly, automatic disconnection of non priority loads.

Technical features

Brand	BTicino
Reference Standard	CEI EN 61558-2-6 - CEI 96-7
Rated voltage	195-264Vac
Input current	28A
Modules	2
Protection class	IP20
Height	83mm
Width	35.6mm
Depth	66mm
Maximum cable section	2.5mm ²
Series	Btdin

Commercial data

Minimum quantity	1
Sales unit	1
EAN code	8005543461174

Technical documentation

? Instruction Sheet

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.