



FC80GT



Smart DIN gateway for remote control via smartphone with the HOME + CONTROL App and / or by voice (using a voice assistant) of lights, shutters, sockets and loads powered by the electrical panel through all the connected products of the Livinglight with Netatmo, Living Now with Netatmo and DIN devices from the BT DIN with Netatmo range (FC80RC, FC80CC and FC80GCS). Zigbee / IP Wi-Fi communication. It can be used as an alternative to the flush-mounted Gateway L / N / NT4500C of the connected Livinglight series and K4500C of the connected Living Now series. Power supply 100-240 V.a.c. - Dimensions 2.5 DIN modules.

Technical features

Brand	BTicino
Rated voltage	100-240Vac
Modules	2.5
Series	Btdin

Commercial data

Minimum quantity	1
Sales unit	1
EAN code	8005543647875

Technical documentation

- ? Installer Manual
- ? Instruction Sheet

- ? Technical Data Sheet

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Complete with



FC80RC
DIN smart relay for light control with m...



F20T60A
Smart DIN meter. It allows to measure th...



FC80CC
Smart DIN contactor suitable for control...



FC80GCS
Connected DIN load management module for...



4141PC
Connected plug&play socket - Directly co...



N4531C
Connected module for socket. When connec...



NT4531C
Connected module for socket. When connec...



L4531C
Connected module for socket. When connec...



4142PC
Mobile connected French/Belgian standard...



3585C
Motion sensor, it controls one or more d...



LN4003CWI
Wireless light switch. It allows the ON ...



LN4027CWI
Rolling shutter wireless switch - It all...




N4003CW
Wireless light switch. It allows the ON ...



L4003CW
Wireless light switch. It allows the ON ...



NT4003CW
Wireless light switch. It allows the ON ...



N4003DCW
Double wireless light switch. It is equi...



NT4003DCW
Double wireless light switch. It is equi...



L4003DCW
Double wireless light switch. It is equi...



LN4570CWI
Home / Away wireless switch. It is equip...



N4575CW
Wireless scenarios control equipped with...




LN4574CWI
Scenario control equipped with 2 buttons...



L4575CW
Wireless scenarios control equipped with...



NT4575CW
Wireless scenarios control equipped with...



N4570CW
Home / Away wireless switch. It is equip...



NT4570CW
Home / Away wireless
switch. It is equip...



L4570CW
Home / Away wireless
switch. It is equip...



N4574CW
Wireless Night&Day
scenario control. Dev...



NT4574CW
Wireless Night&Day
scenario control. Dev...



L4574CW
Wireless Night&Day
scenario control. Dev...



3528C
Pocket remote control 4
scenarios. It al...