



FH81NC6



BTDIN100 - 1P+N thermal-magnetic curve C - In= 6A - Icn= 10kA
- Vn= 230 Vac - 2 modules

Technical features

Brand	BTicino
Reference Standard	CEI EN 60898-1
Rated voltage	230Vac
Input current	6A
Breaking capacity ICN	10kA
Switching curve	C
Modules	2
Poles	1P+N
Protection class	IP20
Height	83mm
Width	35.6mm
Depth	76mm
Maximum cable section	25/35mmq
Series	Btdin

Commercial data

Minimum quantity	3
Sales unit	3
EAN code	8005543472804

Technical documentation

? DWG drawing

? Technical Data Sheet

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Certifications



Complete with



G23A32

Earth leakage module 2P -
type A - In= 3...



G23F32

Earth leakage module 2P -
type F - In= 3...



G23AC32

Earth leakage module 2P -
type AC - In= ...