

#### Distributed by BTicino GENERAL CATALOGUE



# FH84C6



BTDIN100 - 4P thermal-magnetic curve C - In= 6A - Icn= 10kA - Vn= 400 Vac - 4 modules

Commercial data

Brand	BTicino	Minimum quantity	1
Reference Standard	CEI EN 60898-1	Sales unit	1
Rated voltage	400Vac	EAN code	8005543475256
Input current	6A		
Breaking capacity ICN	10kA		
Switching curve	С		
Modules	4		
Poles	4P		
Protection class	IP20		
Height	83mm		
Width	71.2mm		
Depth	76mm		
Maximum cable section	25/35mmq		
Series	Btdin		

#### Technical documentation

? DWG drawing

? Technical Data Sheet

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1999 "R&CTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Source page: https://catalogue.bticino.com/product/low-voltage-energy-distribution/circuit-breakers-for-protection/btdin-miniature-circuit-breakers/btdin100-thermal-magnetic-circuit-breakers-icn-10ka/BTI-FH84C6-EN



## Distributed by BTicino GENERAL CATALOGUE

## Certifications





## Complete with





