



FL4649W



Advanced key card switch, in plastic material (WHITE color). It allows the activation of the hotel room functions with RFID technology recognition, and to control the outside the door DO NOT DISTURB (DND) and "MAKE UP THE ROOM (MUR) notifications. Moreover, based on the information stored on the key card (CUSTOMER or STAFF), it allows to recall different scenarios. Slot for key card with built-in lighting. Connection to SCS-BUS, dimension: 3 modules.

Technical features

Brand	BTicino
Reference Standard	EN 60669-2-1 EN 50491-5-1 EN 50428
Rated voltage	27Vdc
Frequency	RFID (13,56 MHz)
Input current	25mA
Modules	3
Protection class	IP20
Height	93mm
Width	129mm
Depth	48mm
Plant type	BUS-SCS
Robustness	IK04

Operating temperature 0 C +40°C

Colour Bianco

Series

Commercial data

Minimum quantity 1

Sales unit 1

EAN code 8005543625682

Technical documentation

? Technical Data Sheet

? DWG drawing

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.