

## Distributed by BTicino GENERAL CATALOGUE



## FT83C100



BTDIN160 - 3P thermal-magnetic curve C - In= 100A - Icu= 16kA - Vn= 400 Vac - 4,5 modules

Brand	BTicino	Minimum qu
Reference Standard	CEI EN 60947-2	Sales unit
Rated voltage	400Vac	EAN code
Input current	100A	
Breaking capacity ICU	16kA	
Switching curve	С	
Modules	4.5	
Poles	3P	
Protection class	IP20	
Height	83mm	
Width	80.1mm	
Depth	76mm	
Maximum cable section	50/70mmq	
Series	Btdin	

## Commercial data

Minimum quantity	1
Sales unit	1
EAN code	8005543407851

## Technical documentation

- ? DWG drawing
- ? Product Environmental Profile

? Instruction Sheet

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1999 'R&CTE' or where requested also in compliance with 2014/53/EU: 16 April 2014 'RED''. BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Source page: https://catalogue.bticino.com/product/low-voltage-energy-distribution/circuit-breakers-for-protection/btdin-miniature-circuit-breakers/btdin160-thermal-magnetic-circuit-breakers-icu-16ka/BTI-FT83C100-EN