



# FT83D16

BT DIN160 - 3P thermal-magnetic curve D -  $I_n = 16A$  -  $I_{cu} = 16kA$  -  $V_n = 400 V_{ac}$  - 3 modules

## Technical features

Brand	BTicino
Reference Standard	CEI EN 60947-2
Rated voltage	400V <sub>ac</sub>
Input current	16A
Breaking capacity ICU	16kA
Switching curve	D
Modules	3
Poles	3P
Protection class	IP20
Height	83mm
Width	53.4mm
Depth	76mm
Maximum cable section	25/35mm <sup>2</sup>
Series	Btdin

## Technical documentation

? DWG drawing

? Technical Data Sheet

We, BTicino S.p.A. Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Complete with

---



**G33A63**

Earth leakage module 3P -  
type A - In= 6...



**G33AC63**

Earth leakage module 3P -  
type AC - In= ...



**G33F63**

Earth leakage module 3P -  
type F - In= 6...