

## Distributed by BTicino GENERAL CATALOGUE



**Technical features** 

# FV82D16



BTDIN250 - 2P thermal-magnetic curve D - In= 16A - Icu= 25kA - Vn= 400Vac - 2 modules

rectificat reactives		Commercial
Brand	BTicino	Minimum quanti
Reference Standard	CEI EN 60947-2	Sales unit
Rated voltage	400Vac	EAN code
Input current	16A	
Breaking capacity ICU	25kA	
Switching curve	D	
Modules	2	
Poles	2P	
Protection class	IP20	
Height	83mm	
Width	35.6mm	
Depth	76mm	
Maximum cable section	25/35mmq	
Series	Btdin	

### Commercial data

Minimum quantity	3
Sales unit	3
EAN code	8005543701874

### Technical documentation

#### ? DWG drawing

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1999 "R&TE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with testandard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.



# Distributed by BTicino GENERAL CATALOGUE

# Complete with





