



G33F63



Earth leakage module 3P - type F - In= 63A - I_{dn}= 30mA - V_n= 400 Vac

Technical features

Brand	BTicino
Reference Standard	CEI EN 61009-1
Rated voltage	400Vac
Input current	63A
Differential current IDN	0.03A
Differential type	F
Modules	3
Poles	3P
Protection class	IP20
Height	83mm
Width	53.4mm
Depth	76mm
Maximum cable section	25/35mm ²
Series	Btdin

Commercial data

Minimum quantity	1
Sales unit	1
EAN code	8005543614938

Technical documentation

? Instruction Sheet

? DWG drawing

? Technical Data Sheet

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Certifications



Complete with



FA83C40
BTDIN45 - 3P thermal-
magnetic curve C - ...



FA83C50
BTDIN45 - 3P thermal-
magnetic curve C - ...



FA83C63
BTDIN45 - 3P thermal-
magnetic curve C - ...



FH83C40
BTDIN100 - 3P thermal-
magnetic curve C - ...



FH83C50
BTDIN100 - 3P thermal-
magnetic curve C - ...



FH83C63
BTDIN100 - 3P thermal-
magnetic curve C - ...



FH83D40
BTDIN100 - 3P thermal-
magnetic curve D - ...



FH83D50
BTDIN100 - 3P thermal-
magnetic curve D - ...



FH83D63
BTDIN100 - 3P thermal-
magnetic curve D - ...



FN83B40
BTDIN60 - 3P thermal-
magnetic curve B - ...



FN83B50
BTDIN60 - 3P thermal-
magnetic curve B - ...



FN83B63
BTDIN60 - 3P thermal-
magnetic curve B - ...



FN83C40
BTDIN60 - 3P thermal-
magnetic curve C - ...



FN83C50
BTDIN60 - 3P thermal-
magnetic curve C - ...



FN83C63
BTDIN60 - 3P thermal-
magnetic curve C - ...



FN83D40
BTDIN60 - 3P thermal-
magnetic curve D - ...



FN83D50
BTDIN60 - 3P thermal-
magnetic curve D - ...



FN83D63
BTDIN60 - 3P thermal-
magnetic curve D - ...



FT83C40
BTDIN160 - 3P thermal-
magnetic curve C - ...



FT83C50
BTDIN160 - 3P thermal-
magnetic curve C - ...



FT83C63
BTDIN160 - 3P thermal-
magnetic curve C - ...



FT83D63
BTDIN160 - 3P thermal-
magnetic curve D - ...



FT83D6
BTDIN160 - 3P thermal-
magnetic curve D - ...



FT83D10
BTDIN160 - 3P thermal-
magnetic curve D - ...



FT83D16
BTDIN160 - 3P thermal-
magnetic curve D -...



FT83D20
BTDIN160 - 3P thermal-
magnetic curve D -...



FT83D25
BTDIN160 - 3P thermal-
magnetic curve D -...



FT83D32
BTDIN160 - 3P thermal-
magnetic curve D -...



FT83D40
BTDIN160 - 3P thermal-
magnetic curve D -...



FT83D50
BTDIN160 - 3P thermal-
magnetic curve D -...