



G43A63

bticino

Earth leakage module 4P - type A - $I_n = 63A$ - $I_{dn} = 30mA$ - $V_n = 400V_{ac}$

Technical features

Brand	BTicino
Reference Standard	CEI EN 61009-1
Rated voltage	400Vac
Input current	63A
Differential current IDN	0.03A
Differential type	A
Modules	3
Poles	4P
Protection class	IP20
Height	83mm
Width	53.4mm
Depth	76mm
Maximum cable section	25/35mmq
Series	Btdin

Commercial data

Minimum quantity	1
Sales unit	1
EAN code	8005543463086

Technical documentation

[? Instruction Sheet](#)
[? Technical Data Sheet](#)

We, BTicino S.p.A. Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Complete with



FA84C40

BTDIN45 - 4P thermal-magnetic curve C - ...



FA84C50

BTDIN45 - 4P thermal-magnetic curve C - ...



FA84C63

BTDIN45 - 4P thermal-magnetic curve C - ...



FH84C40

BTDIN100 - 4P thermal-magnetic curve C - ...



FH84C50

BTDIN100 - 4P thermal-magnetic curve C - ...



FH84C63

BTDIN100 - 4P thermal-magnetic curve C - ...



FH84D40

BTDIN100 - 4P thermal-magnetic curve D - ...



FH84D50

BTDIN100 - 4P thermal-magnetic curve D - ...



FH84D63

BTDIN100 - 4P thermal-magnetic curve D - ...



FN84B40

BTDIN60 - 4P thermal-magnetic curve B - ...



FN84B50

BTDIN60 - 4P thermal-magnetic curve B - ...



FN84B63

BTDIN60 - 4P thermal-magnetic curve B - ...



FN84C40

BTDIN60 - 4P thermal-magnetic curve C - ...



FN84C50

BTDIN60 - 4P thermal-magnetic curve C - ...



FN84C63

BTDIN60 - 4P thermal-magnetic curve C - ...



FN84D40

BTDIN60 - 4P thermal-magnetic curve D - ...



FN84D50

BTDIN60 - 4P thermal-magnetic curve D - ...



FN84D63

BTDIN60 - 4P thermal-magnetic curve D - ...



FT84C40

BTDIN160 - 4P thermal-magnetic curve C - ...



FT84C50

BTDIN160 - 4P thermal-magnetic curve C - ...



FT84C63

BTDIN160 - 4P thermal-magnetic curve C - ...