

G43XAC125



Earth leakage module 4P - type AC - $I_n = 125A$ - $I_{dn} = 30mA$ - $V_n = 400V_{ac}$

Technical features

Brand	BTicino
Reference Standard	CEI EN 60947-19
Rated voltage	400Vac
Input current	125A
Differential current IDN	0.03A
Differential type	AC
Modules	6
Poles	4P
Protection class	IP20
Height	83mm
Width	107.2mm
Depth	76mm
Maximum cable section	50/70mmq
Series	Btdin

Commercial data

Minimum quantity	1
Sales unit	1
EAN code	8005543414088

Technical documentation

? Instruction Sheet

? Technical Data Sheet

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Complete with



FT84C100
BTDIN160 - 4P thermal-
magnetic curve C -...



FT84C125
BTDIN160 - 4P thermal-
magnetic curve C -...



FT84C80
BTDIN160 - 4P thermal-
magnetic curve C -...



FT84D100
BTDIN160 - 4P thermal-
magnetic curve D -...



FT84D125
BTDIN160 - 4P thermal-
magnetic curve D -...



FT84D80
BTDIN160 - 4P thermal-
magnetic curve D -...



FV84C100
BTDIN250 - 4P thermal-
magnetic curve C -...



FV84C125
BTDIN250 - 4P thermal-
magnetic curve C -...



FV84C80
BTDIN250 - 4P thermal-
magnetic curve C -...



FV84D125
BTDIN250 - 4P thermal-
magnetic curve D -...



FV84D100
BTDIN250 - 4P thermal-
magnetic curve D -...



FV84D80
BTDIN250 - 4P thermal-
magnetic curve D -...



FT84D16
BTDIN160 - 4P thermal-
magnetic curve D -...



FT84D20
BTDIN160 - 4P thermal-
magnetic curve D -...



FT84D25
BTDIN160 - 4P thermal-
magnetic curve D -...



FT84D32
BTDIN160 - 4P thermal-
magnetic curve D -...



FT84D40
BTDIN160 - 4P thermal-
magnetic curve D -...



FT84D50
BTDIN160 - 4P thermal-
magnetic curve D -...



FT84D63
BTDIN160 - 4P thermal-
magnetic curve D -...



FV84D16
BTDIN250 - 4P thermal-
magnetic curve D -...



FV84D20
BTDIN250 - 4P thermal-
magnetic curve D -...



FV84D25
BTDIN250 - 4P thermal-
magnetic curve D -...



FV84D32
BTDIN250 - 4P thermal-
magnetic curve D -...



FV84D40
BTDIN250 - 4P thermal-
magnetic curve D -...

**FV84D50**BTDIN250 - 4P thermal-
magnetic curve D -...**FV84D63**BTDIN250 - 4P thermal-
magnetic curve D -...