



G701T/300A



Toroid for earth leakage relay item G701/2 diameter 300 mm -
Idn=1A - In=2000A

Technical features

Brand	BTicino
Reference Standard	IEC 755
Input current	630A
Differential current IDN	1A
Protection class	IP20
Diameter	310mm
Maximum cable section	2.5mmq
Series	Btdin

Commercial data

Minimum quantity	1
Sales unit	1
EAN code	8012199383194

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Complete with



G701N

Earth leakage relay with
separate toroid...



G701Q

Earth leakage relay with
separate toroid...