



## HC4434



Green Switch: switch with passive infrared movement sensor – brightness sensor with adjustable threshold and adjustable switch off delay time - manual switching on of the light using the front pushbutton, and automatic switching off based on brightness levels and movement – 2.5 A resistive/inductive relay output – 230 Vac power supply - 2 modules

### Technical features

Brand	BTicino
Rated voltage	100-240Vac
Frequency	50-60Hz
Modules	2
Contact type	1,7 A
Protection class	IP20
Illuminance level	5-1275 lux
Colour	Chiaro
Series	Axolute

### Commercial data

Minimum quantity	1
Sales unit	1
EAN code	8005543442517

### Technical documentation

? Instruction Sheet	? Safety prescriptions
? Instruction Sheet	? DWG drawing

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.