K4430

Switch with passive infrared ray movement sensor, suitable for all types of load including LED lamps - 2 wires – variable threshold twilight circuit with possibility of exclusion – timing circuit to delay switching off adjustable from 10 seconds to 10 minutes - it has a selector switch for operating type ON - AUTO - OFF. It is possible to choose between two types of configuration: 1) visible selector switch: use the covers KW17SL / KG17SL / KM17SL which include the additional plastic switch 2) hidden selector switch: use the covers KW17 / KG17 / KM17 Power supply 230 Vac - 2 modules

Technical features

Brand	BTicino
Rated voltage	230Vac
Frequency	50-60Hz
Input current	20mA-1A
Rated power (W)	3-250W
Modules	2
Protection class	IP20
Plant type	stand alone
Series	Living Now

Commercial data

Minimum quantity	1
Sales unit	1
EAN code	8005543612538

Technical documentation

? Technical Data Sheet

Complete with

KW17
Covers for 2-module IR switches without ...

KG17
Covers for 2-module IR switches without ...

KM17
Covers for 2-module IR switches without ...

KW17SL
Covers for IR switches item K4430 (versi...

KG17SL
Covers for IR switches item K4430 (versi...

KM17SL
Covers for IR switches item K4430 (versi...