



K4431

bticino

Switch with passive infrared ray movement sensor, suitable for all types of load including LED lamps - 3 wires – variable threshold twilight circuit with possibility of exclusion – timing circuit to delay switching off adjustable from 30 seconds to 10 minutes - 230 V.a.c. power supply - 1 module

Technical features

Brand	BTicino
Rated voltage	230Vac
Frequency	50-60Hz
Rated power (W)	460W
Modules	1
Contact type	2A
Robustness	IP20

Series

Commercial data

Minimum quantity	1
Sales unit	1
EAN code	8005543612552

Technical documentation

? Technical Data Sheet	? Technical Data Sheet
? Instruction Sheet	? Technical Data Sheet

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Complete with


KW16

Covers for 1-module IR switch. For item ...


KG16

Covers for 1-module IR switch. For item ...


KM16

Covers for 1-module IR switch. For item ...