



K4659

bticino

Green Switch: passive IR movement sensor, suitable for the detection of presence in transit areas (corridors, toilets, service rooms). Operating mode (automatic or manual), time delay (5s to 59min), and brightness threshold (20 to 1275 LUX) settable using the advanced/basic (BMSO4001/BMSO4003) configuration remote control - 2 modules.

Technical features

Brand	BTicino
Rated voltage	27Vdc
Input current	15mA
Modules	2
Protection class	IP20
Robustness	IK04

Illuminance level 20-1275 lux

Series

Commercial data

Minimum quantity	1
Sales unit	1
EAN code	8005543615102

Technical documentation

? Technical Data Sheet

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Complete with



KW17
Covers for 2-module IR switches without ...



KG17
Covers for 2-module IR switches without ...



KM17
Covers for 2-module IR switches without ...



BMSO4003
Remote control for the configuration (ba...



088240
The base with the smartphone installed b...