



KG8011



FULL control. Touch digital control for the management of one to three functions among the following: on/off, dimmer, up/down shutter without preset, scenarios and load control. It can also be used as group or general control. On-board proximity sensor that allows the display of function icons when approaching the control - 1 module. Black.

Technical features

| | |
|---------------|--------------------|
| Brand | BTicino |
| Rated voltage | 27Vdc |
| Input current | 9mA |
| Modules | 1 |
| Series | MyHome, Living Now |

Commercial data

| | |
|------------------|---------------|
| Minimum quantity | 5 |
| Sales unit | 5 |
| EAN code | 8005543645970 |

Technical documentation

? [Technical Data Sheet](#)

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Complete with



KG8102P1
Electrified frame with
intermediate cont...



KG8103
Electrified frame with
intermediate cont...



KG8103P1
Electrified frame with
intermediate cont...



KG8104
Electrified frame with
intermediate cont...



KG8104P1
Electrified frame with
intermediate cont...



KG8103M24
Electrified frame with anti-
theft reader...



KG8104M02
Electrified frame with
double socket Ita...



KG8104M24
Electrified frame with anti-
theft reader...



KG8104M03
Electrified frame with
standard Italian ...



KG8103M02
Electrified frame with
double Italian so...



KG8103M03
Electrified frame with
Italian and Germa...



K8001
Connection module. Device
for the power ...



K8002L
Flush mounted actuator,
with 2 independe...



K8002S
Shutter actuator with 2
relays 2 A 250 V...