



# LN4691



Flush mounted thermostat with backlit display. It can be used to control the temperature of an individual zone, irrespective of a central unit being installed as part of the system or not. It features a temperature probe and an input for the connection of a contact line (e.g. window contact). It can be used for the management of different types of systems, and the adjustment of the fan speed when fan coils are used. Possibility of automatic operation (summer/winter), with compatible systems. SCS bus connection – 2 modules

## Technical features

Brand	BTicino
Reference Standard	EN 60669-2-1EN 50491-5-1EN 50428
Rated voltage	27Vdc
Input current	30mA
Modules	2
Series	Livinglight, MyHome

## Commercial data

Minimum quantity	1
Sales unit	1
EAN code	8005543498057

## Technical documentation

? Installer Manual	? Technical Data Sheet
? DWG drawing	? Software Manual
? PEP certification	? User Manual

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

## Complete with

**F430/2**

2 independent relay  
actuator – for singl...

**F430V10**

Actuator with 2 x 0-10 Volt  
outputs for ...

**F430/4**

4 independent relay  
actuator - for singl...

**F430R8**

Actuator with 8  
independent relays for t...

**F430R3V10**

Actuator with 3  
independent relays and 2...