



M7TIC/IO



Module to be configured using a set of configurators (item 3501K) – 24 inputs for the detection of change of status of signals coming from clean contacts, 4 analogue inputs (4-20mA) for the connection of sensors (temperature, pressure etc...), 6 relay NO outputs with 230V contacts, 2A and side expansion port – communication network with MODBUS protocol through RS485 physical connection. $V_n = 24 \text{ Vac/dc}$ - 6 DIN modules

Technical features

| | |
|---------------|---------------------------|
| Brand | BTicino |
| Rated voltage | 24Vac/dc |
| Modules | 6 |
| Series | Measuring and supervision |

Commercial data

| | |
|------------------|---------------|
| Minimum quantity | 1 |
| Sales unit | 1 |
| EAN code | 8012199713168 |

Technical documentation

? [Instruction Sheet](#)

? [Parameter Table](#)

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU; 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU; 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU; 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.