





MW7237

bticino

DIN35 plate for installation of Megaswitch

Technical features

BTicino Brand

Series **MEGASWITCH**

Commercial data

Minimum quantity 1

Sales unit 1

EAN code 8012199560151

Technical documentation

? Safety prescriptions

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The optimizance are be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Complete with



T7233WF/160 Disconnector MW250 - 3P - 160A - 690Vac...



T7233WF/160B Disconnector for auxilary accessories MW...



T7233WF/200 Disconnector MW250 - 3P 200A - 690Vac...



T7233WF/200B Disconnector for auxilary accessories MW...



T7233WF/250 Disconnector MW250 - 3P - 250A - 690Vac...



T7233WF/250B Disconnector for auxiliary accessories MW...



T7234WF/160 Disconnector MW250 - 4P - 160A - 690Vac...



T7234WF/160B Disconnector for auxilary accessories MW...



Disconnector MW250 - 4P

megaswitch/BTI-MW7237-EN





T7234WF/250 Disconnector MW250 - 4P



T7234WF/250B Disconnector for auxilary