



N4027CW



Wireless shutter control. It allows control of one or more shutter controls. Surface installation with repositionable adhesives (supplied as standard), or inside flush mounted boxes. Built-in battery exhausted LED. CR2032 type 3 V power battery with 8 year expected life supplied (as standard) - 2 modules.

Technical features

Brand	BTicino
Rated voltage	3Vdc
Modules	2
Series	Livinglight

Commercial data

Minimum quantity	1
Sales unit	1
EAN code	8005543642238

Technical documentation

[? Technical data sheet](#)[? Instruction Sheet](#)

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Complete with



4027C
Connected micromodule
for shutters. Asso...



N4027C
Connected shutter control.
It controls a...



N4510C
Gateway. This pack enables
to create a c...