



## NT4003CW



Wireless light switch. It allows the ON / OFF and dimming control of one or more connected devices for the lighting control. Surface installation with repositionable stickers (supplied) or onto a flush mounting box without any wiring. The battery can be replaced without removing it from the supporting frame. Integrated LED for low battery indication. Powered by battery 3V type CR2032 (supplied) with an autonomy of 8 years - 2 modules.

### Technical features

|               |             |
|---------------|-------------|
| Brand         | BTicino     |
| Rated voltage | 3Vdc        |
| Modules       | 2           |
| Series        | Livinglight |

### Commercial data

|                  |               |
|------------------|---------------|
| Minimum quantity | 1             |
| Sales unit       | 1             |
| EAN code         | 8005543642184 |

### Technical documentation

? Technical data sheet

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU; 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU; 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

### Complete with

|   |   |   |   |
|---|---|---|---|
|  <p><b>NT44TIC</b><br/>Dimmer/switch. It allows to control ligh...</p> |  <p><b>NT4003C</b><br/>Connected two-way switch. It allows to c...</p> |  <p><b>4141PC</b><br/>Connected plug&amp;play socket - Directly co...</p> |  <p><b>NT4531C</b><br/>Connected module for socket. When connec...</p> |
|  <p><b>NT4510C</b><br/>Gateway. This pack enables to create a c...</p> |  <p><b>FC80GT</b><br/>Smart DIN gateway for remote control via...</p>  |  <p><b>NT4500C</b><br/>Gateway. This pack enables to create a c...</p>    |   |