





NT4180/3



Socket triplex 2P+T 10/16A 250 Vac - centre distance 19mm and 26mm - shielded tulip contacts - Tech

Technical features

| Brand | BTicino |
|---------------|-------------|
| Rated voltage | 250Vac |
| Input current | 10-16A |
| Modules | 3 |
| Poles | 2P+T |
| Contact type | 2P+T |
| Series | Livinglight |

Commercial data

| Minimum quantity | 5 |
|------------------|---------------|
| Sales unit | 5 |
| EAN code | 8012199482446 |

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

Complete with



150647NA POP-UP box - 4 living light modules , m...



150647NG POP-UP box - 4 living light modules , m...



150647NS POP-UP box - 4 living light modules , m...



123006AL Kit for workstation 8 modules aluminium...

