



## NT4659N



Green Switch: passive infrared motion sensor (PIR), suitable for motion detection in traffic areas (hallways, bathrooms, utility rooms). Mode of operation (automatic or manual), delay time (from 5s to 59min) and brightness threshold (from 20 to 1275 lux) settable by means of advanced/basic configuration remote control (BMSO4001/BMSO4003), physical or virtual configuration. 2 modules.

### Technical features

Brand	BTicino
Rated voltage	27Vdc
Input current	15mA
Modules	2
Protection class	IP20
Robustness	IK04

Illuminance level	20-1275 lux	Commercial data	
Operating temperature	-5°C +45°C	Minimum quantity	1
Colour	Tech	Sales unit	1
Series	MyHome, Livinglight	EAN code	8005543442654

### Technical documentation

? Instruction Sheet	? Technical Data Sheet
? Instruction sheet	? DWG drawing

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1995/5/CE: 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU: 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.