



# T7314MA

bticino

MS250 disconnecter 4P - In=250A - Ue= 690Vac

## Technical features

Brand	BTicino
Reference Standard	CEI EN 60947-2
Rated voltage	690Vac
Input current	250A
Breaking capacity ICU	100kA
Poles	4P
Height	200mm
Width	140mm
Depth	105mm
Series	MEGATIKER

## Commercial data

Minimum quantity	1
Sales unit	1
EAN code	8012199200118

## Technical documentation

? Instruction Sheet

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU; 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU; 26 February 2014, and/or where requested also in compliance with 1995/5/CE; 9 March 1999 "R&TTE" or where requested also in compliance with 2014/53/EU; 16 April 2014 "RED". BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.

## Complete with



**T7071/250**

GL250 underneath earth leakage module fo...



**T7072/250**

GS250 underneath earth leakage module fo...



**T7073/250**

GF250 underneath earth fault module for ...



**M7025**

Padlock block for MA/MH160, MS200 and MA...



**M7295**

Terminal shields to install between the ...