

Distributed by BTicino GENERAL CATALOGUE



T733L40

bticino

M3 250L - thermal-magnetic circuit breaker 3P - Icu= 100kA - In= $40\mathrm{A}$

Technical features		Commercial data	
Brand	BTicino	Minimum quantity	1
Reference Standard	CEI EN 60947-2	Sales unit	1
Rated voltage	690Vac	EAN code	8005543683965
Frequency	50-60Hz		
Input current	40A		
Breaking capacity ICU	100kA		
Poles	3P		
Protection class	IP20/40		
Height	165mm		
Width	105mm		
Depth	93mm		
Series	MEGATIKER		

Technical documentation

? Technical Data Sheet

? Instruction Sheet

We, BTicino S.p.A Viale Borri 231 21100 Varese (Italy), declare that all items listed in BTicino catalogues, have been manufactured in compliance with the principal elements of safety objectives of European Directive said LVD: 2014/35/EU: 26 February 2014 and, where requested, also in compliance with essential protection requirements of electromagnetic compatibility according to European Directive 2014/30/EU: 26 February 2014, and/or where requested also in compliance with 1999 'R&CTTE'' or where requested also in compliance with 2014/53/EU: 16 April 2014 'RED'', BTicino S.p.A. products are in compliance with the standard published by the International Electrotechnical Commission (IEC). The compliance can be proved by Certificates issued by organizations recognized by IEC according to the CB-scheme. Our items comply with relevant European Product- Standards and show, whether provided, CE marking, they have been constructed in accordance with good engineering practice in safety matters in force in the Community, they do not endanger the safety of persons, domestic animals or property when properly installed and maintained and used in applications for which they were made.